



MixRiteTM

PROPORTIONAL INJECTOR PUMPS

For the injection of chemicals & minerals into Pressurised water lines

- Accurate injection into any pressure waterline
- No power or water meter required
- Simple installation, operation and service
- Suitable for injection of bloat oil, copper, zinc, salt and many other mineral
- High UV resistance





MixRite 2502

Rate of additive: 0.3 - 2.0%

Water Pressure: 0.2 - 8 bar (3 - 120 PSI)

Flow rate: 20 - 2500 l/h

Coupling: 3/4"



MixRite 2504

Rate of additive: 0.4 - 4.0%

Water Pressure: 0.2 - 8 bar (3 - 120 PSI)

Flow rate: 30 - 2500 l/h

Coupling: 3/4"



MixRite 2508

Rate of additive: 0.1 - 0.9%

Water Pressure: 0.2 - 8 bar (3 - 120 PSI)

Flow rate: 20 - 2500 l/h

Coupling: 3/4"



TF-5

Flow Rate: 0.2 - 5 m³/h (1 - 22 GPM)

TF-5-002: 0.2 - 2.0% Ratio

Water pressure: 1 - 8 bar (15 - 120 PSI)

Coupling: 1" BSP



TF-10

Flow Rate: 0.5 - 10 m³/h (2 - 45 GPM)

TF-10-002: 0.2 - 2.0% Ratio

TF-10-005: 0.5 - 5.0% Ratio

Water pressure: 1 - 8 bar (15 - 120 PSI)

Coupling: 1.5" BSP



TF-25

Flow Rate: 2 - 25 m³/h (5 - 110 GPM)

TF-25-002: 0.2 - 2.0% Ratio

TF-25-005: 0.5 - 5.0% Ratio

Water pressure: 1 - 8 bar (15 - 120 PSI)

Coupling: 2" BSP



TEFEN
Advanced Plastic Solutions
www.tefenplastic.com